

Ute Deck Stabilised Tipping System c/w 12V Power Pack and Accessories



Item No.	Qty	Part Code	Description	Details
1	1	AFH-500-01-009	Rear hinge kit	Cast light weight easy fit rear hinge kit, rated to 3.5t.
2	1	PWP-12VDC-03L	Power Pack	12V DC 800 watt power pack with 120bar relief and thermal cut-off
3	1	A5HK	Hose Kit	High pressure hydraulic hose kit with crimped fittings and adaptors
4	1	34-355	Switch	Dash mount electrical rocker switch
5	1	9F600S	Flow control	Dial up control valve to control tip body decent speed
6	1	A5 c/w A5 Breather	Tipping Mechanism	Genuine HARSH USA stabilised tipping mechanism

Typical Advantages:

The system will lift 1600kgs of body and payload to a 45° tip angle when fitted to a 2.4m body with a 1194mm bottom pivot centre and a 300mm overhang. Shortening of the bottom pivot will increase tip angle but reduce payload.

The patented HARSH USA stabiliser mechanism ensures a safe stable load lift whilst the Hydroven power pack safety features protect the hydraulic system from overloading.

The price of components and cost of installation makes the NZH system the best value for money over single acting cylinder applications or copy cat systems.

Notes: Use part code A5 – UTE – K2 to order a complete system without the rear hinge kit.

Quote Ref:

Date:

NZ\$



THS

TRANSPORT
HYDRAULIC
SOLUTIONS

TM

INNOVATION IN MOTION

FREEPHONE

New Zealand **0800 22 55 69**

Australia **1800 22 55 69**

www.transporthydraulics.com